

569.00 EUR
incl. 19% VAT, plus [shipping](#)



- Elkhart Lake J6412 Processor !
- 6x LAN !
- HBJC903I05 !

- Intel® Elkhart Lake J6412 Processor
- Support 1* DDR4 3200 up to 32GB
- 6* Intel® I225-V 2.5GbE
- 1* M.2 M-key (2242, SATA interface) support NVMe
- 1* M.2 E-key (2230, USB2.0/PCIe Gen.3 x1 interface)
- 1* M.2 B-key (3042, USB3.1/PCIe Gen.3 x1 interface)
- 1* USB3.1 (Gen.2), 1* USB2.0, 3* COM, 1* HDMI, 1* RS232(RJ45 TYPE)
- Fan-less cooling design
- Adapter DC12V_60W

| | | |
|-------------|--|--|
| Model | – HBJC903I05-6412 (Default) – HBJC903I05I-6412 (Wifi) | |
| CPU/Chipset | – Intel® Elkhart Lake SoC Processor (J6412 , 4C/2.0GHz, TDP 10W) | |
| BIOS | – AMI 128Mb Flash ROM | |
| Memory | – 1* DDR4 3200MHz SO-DIMM up to 32GB | |
| Network | – 6* Intel® i225-V 2.5GbE | |
| Graphics | – Intel® HD Graphics, shared memory – 1* HDMI 1.4b (Max Resolution: 3840x2160@30Hz) – Support Single Display | |
| Storage | – 1* M.2 M-key (2242, SATA interface) support NVMe – 1* 2.5" SATAIII Device | |
| Expansion | – 1* M.2 E-key (2230, USB2.0/PCIe Gen.3 x1 interface) – 1* M.2 B-key (3042, USB3.1/PCIe Gen.3 x1 interface) | |

| | |
|--------------------|--|
| Rear Panel I/O | <ul style="list-style-type: none"> - 1* USB 3.1 (Gen.2) - 1* USB 2.0 - 6* RJ45 - 1* Console RS232 (RJ45 TYPE) - 3* COM (1* RS232/422/485, 2* RS232) - 1* HDMI - 1* Power LED, 1* HDD LED - 1* Power Button - 1* DC-in Jack (Lockable) - 2* Antenna (Optional) - 1* GND Hold |
| Front Panel I/O | - N/A |
| Internal Connector | - SIM Card Holder |
| Power Source | <ul style="list-style-type: none"> - MB : DC-in 12V - Adapter : DC12V_60W |
| Compliance | - CE, FCC, RoHS, ErP Ready |
| Dimensions | <ul style="list-style-type: none"> - System: 200 (W) x 180 (D) x 59.5 (H) mm - Box: 287 (W) x 122 (D) x 280 (H) mm - Net Weight: 2.26KG - Gross Weight: 3.26KG |
| Temperature | <ul style="list-style-type: none"> - Operating Temperature: -20 ~ 60° C - Storage Temperature: -20 ~ 60° C - Humidity: 10% ~ 90% RH @40°C (non-condensing) |
| OS Support | - Windows 10, Windows 11, Linux |