



409.00 EUR
incl. 19% VAT, plus [shipping](#)

- Intel Elkhart Lake SoC !
- HB368F21 !

- Intel Elkhart Lake SoC Processor
- 1* DDR4 3200MHz SO-DIMM up to 32GB
- 2* USB3.1 (Gen.2), 4* USB2.0, 2* RJ45, 1* Audio (MIC + Line-out), 1* Line-IN, 3* DP, 2* COM, 1* GPIO
- 160.2*106*43.5 mm
- DC12V_60W Adapter
- Support TPM2.0 (option)

Model	– HB368F21-6412-W (non-WiFi) – HB368F21I-6412-W (WiFi)	
CPU/Chipset	– Intel® Elkhart Lake SoC Processor (J6412 , TDP 10W)	
BIOS	– AMI Flash ROM	
Memory	– 1* DDR4 3200MHz SO-DIMM up to 32GB	
Network	– 2* Realtek RTL8119I GbE	
Graphics	– Intel® HD Graphics, shared memory – 3* DP (Max Resolution: 4096x2160@60Hz) – Support Triple Displays	
Storage	– 1* M.2 M-key (2242/2280, PCIe Gen.3 x2/SATA interface) support NVME – 32GB eMMC onboard (option)	
Expansion	– 1* M.2 E-key (2230, PCIe Gen.3 x1/USB2.0 interface) – 1* M.2 B-key (3042, USB3.0 interface)	

Rear Panel I/O	<ul style="list-style-type: none"> - 2* RJ45 - 2* USB3.1(Gen.2) - 1* USB2.0 - 1* 8 bit GPIO (Phoenix Connector 2*9 PIN) - 2* RS232/422/485 (Phoenix Connector 2*9 PIN) - 1* DC in (Lockable)
Front Panel I/O	<ul style="list-style-type: none"> - 1* Power button + Power LED - 4* USB2.0 - 1* Audio(Line out+MIC) - 1* Line in - 3* DP
Internal Connector	<ul style="list-style-type: none"> - SIM Card Holder
Power Source	<ul style="list-style-type: none"> - Adapter : AC 90~240V input / DC12V_60W output - MB : DC12~36V input
Compliance	<ul style="list-style-type: none"> - CE, FCC, LVD, RoHS, ErP Ready
Dimensions	<ul style="list-style-type: none"> - System: 160.2 (W) x 106 (D) x 43.5 (H) mm - Net Weight: 1.01KG: Gross Weight: 1.52KG
Temperature	<ul style="list-style-type: none"> - Operating Temperature: -20 ~ 80° C (Under the condition of using M.2 interface SSD) - Storage Temperature: -20 ~ 60° C - Humidity: 10% ~ 90% RH @40°C (non-condensing)
OS Support	<ul style="list-style-type: none"> - Windows 11, Linux