



389.00 EUR
 incl. 19% VAT, plus [shipping](#)

- 12VDC based !
- 4x LAN ports

CARTFT.COM

Support: [Assembling Tutorial \[DE\]](#) | [Assembling Tutorial \[EN\]](#)

CarPC-barebone for use with Intel Pentium-M/Celeron-M CPU.

CALU specifications	
Processor (supported)	Intel Pentium M processor or Celeron M processor (Dothan or Banias) 1.3GHz or higher
Memory	Supports DDR 400/333/266 DIMM RAM 0.8" low profile 2x memory slots ! Maximum : 2 GB
Video	Intel Extreme Graphics 2 Supports up to 64MB DVMT video memory
Audio	Software AC '97 Audio CODEC
Peripheral Connection	Front : 3 x RJ45 10/100Mb Fast Ethernet 1 x IEEE 1394 Firewire port 1 x USB 2.0 / 1.1 Port 1 x MIC Port 1 x Ear Phone output Jack Power-on button Reset button Power-on and HDD LED Rear : 1 x RS232 COM port 1 x parallel printer port 1 x RJ45 10/100Mb Fast Ethernet 1 x Line-Out output Jack 2 x USB 2.0 / 1.1 Ports 1 x 15 pin VGA 1 x 12v DC Power Jack input
Storage	One 2.5 inch Hard Disk and 9.5mm high. (Support Ultra DMA 33/66/100).
Weight & Size	System approximately 3kg (fully equipped). System Dimension: 155 x 255 x 55 mm
Power req.	12V, 5A

Accessory

Storage	Supports all Standard Slim CD-ROM/DVD-ROM, CD-RW, DVD-RW Combo Supports all 2.5" standard IDE hard drive, ATA-100/66/33.
Scope of supply	110V/230V EU power supply Barebone CPU Kühlkörper

Graphics driver for 800x480 resolution : [Here](#)